



SPECIFICATION

- 3 band EQ on mono input and 2 band EQ on stereo input
- 1 Aux send for external effects and monitoring
- Peak LED on all input
- MUTE and SOLO switch on all input
- Built in 99 program digital effect
- USB interface for MP3 input and playback with digital display
- USB interface for connect mixer to PC
- BLUETOOTH function
- Recording function
- 7 band graphic EQ
- +48V phantom power supply

SPECIFICATION :

THD	0.004% (mic input)
.....	0.01% (line input)
.....	0.01% (stereo input)
Signal to Noise Ratio	94dB (mic input)
.....	73dB (line input)
.....	84dB (stereo input)

Frequency Response 20Hz - 20KHz
Equalization : High ± 15dB, 12KHz
 : Mid ± 15dB, 2.5KHz
 : Low ± 15dB, 80Hz

SMK6

6 Channel input mixer
(4 Mono input & 1 Stereo input)

SMK8

8 Channel input mixer
(6 Mono input & 1 Stereo input)



บริษัท เอ็นทีเอส อิเล็คทรอนิกส์ โซลูชั่น จำกัด

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์ : 02-4387023 ถึง 4, 02-4377639 โทรสาร : 02-4371897

www.nts-solution.com



 NtsElectronicSolution



 NtsElectronicSolution  @ntssolution